



Females (2): **M** D-2 **H** Core: 58-62 HRC, Surface: 80 HRC **S** Titanium Nitride Coated

Male: **M** H-13 **H** 42-48 HRC **S** Salt Bath Nitrided

▶ CAD insertion point

CATALOG NUMBER	T +.000 -.002	W +.0000 -.0004	X +.000 -.005	A +.000 -.002	C	D .0001/.0002 Clearance Per Side	R Pocket Radius	S ±.01	P +.001 -.000	SHCS
SLX50X87	.500	2.000	.875	1.375	.87	.750	.187	.312	.250	#10-32 x 5/8"
SLX75X137	.750	3.000	1.375	1.875	1.18	1.250	.250	.375	.313	1/4-20 x 3/4"
SLX75X187	.750	3.000	1.875	1.875	1.18	1.250	.250	.375	.313	1/4-20 x 3/4"
SLX100X137	1.000	4.000	1.375	2.375	1.43	1.500	.500	.500	.375	3/8-16 x 1"

Screws included.

For custom Locks, refer to the templates in section X.

Lubrication:

- For packaging and storage lubrication, Setral food grade grease is applied to all areas, including the particle rings.
- For production, install the locks and wipe down the outside of the X-Style Locks only; maintain the grease on the mating surfaces and within the rings.